

# **HISTORY OF THE FORT LEWIS INCINERATOR: LESSONS LEARNED**

Rudy M. Verzuh  
Fort Lewis Public Works  
Fort Lewis, WA  
253-967-2763  
FAX: 253-967-9333  
Email: [verzuhr@lewis.army.mil](mailto:verzuhr@lewis.army.mil)

William T. Morgan, P.E.  
Lockwood Greene Technologies, Inc.  
250 Williams Street, Suite 2350  
Atlanta, GA 30303  
404-654-4439  
FAX: 404-654-4437  
Email: [bmorgan@lgt.lg.com](mailto:bmorgan@lgt.lg.com)

Douglas C. Smith, P.E.  
Bouillon, Inc.  
700 5<sup>th</sup> Avenue, Suite 5800  
Seattle, WA 98104  
206-682-3910  
FAX: 206-682-3916  
Email: [dcsmith@bouillon.com](mailto:dcsmith@bouillon.com)

## **ABSTRACT**

The U.S. Army installation at Fort Lewis near Tacoma, Washington, completed in 1996 construction of a 163.3 Mg (180 ton) per day mass-burning, steam-generating incinerator. This plant was equipped with acid gas control equipment, but it was unable to consistently control acid gas emissions and flue gas temperatures. Design and equipment deficiencies included lack of independent control of acid gas emissions and flue gas temperature. The plant was also unable to deliver lime slurry at the proper concentration and rate. By retrofitting the acid gas control system with smaller lime slurry pumps and modified controls, The Fort Lewis Waste-to-Energy Plant was then able to consistently meet regulatory requirements for acid gas emissions and flue gas temperature.

## **INTRODUCTION**

### **Plant Description**

The Fort Lewis Waste-to-Energy Plant is located on the Fort Lewis Army installation near Tacoma, Washington. The plant burns solid waste generated from Fort Lewis, McChord Air Force Base, Bangor Submarine Base, Madigan Army Medical Center, and the Veterans Administration Hospital in Lakewood, Washington. It generates steam used for heat and hot water at Fort Lewis. It is owned and operated by the United States Army, Headquarters I Corps and Fort Lewis Public Works Directorate. The plant consists of three 54.4 Mg (60 ton) per day municipal waste, mass burn steam generating incinerator units. Each unit is equipped with a Keeler Dorr Oliver water wall boiler rated at 10,206 kg (22,500 lb) per hour of saturated steam at 7.73 kg/cm<sup>2</sup> (110 lb/in<sup>2</sup>).